

Card Reader

ULTIMATE PRO SD & microSD UHS-II Dual Slot Card Reader

USB3.2 Gen1x1 Type-C

DGP2023 Record Item Division Card Reader/Writer Gold Award Winner

- Supports maximum 312MB/s high-speed transfer with SD & microSD UHS-II compatible cards
- Supports maximum 200MB/s high-speed transfer with SD & microSD UHS-I DDR200 compatible cards
- Plug and play, simply connect to the device
- Includes 1 USB-C to C cable and 1 USB-A to C cable
- The body is made of high-quality aluminum alloy, which is sturdy, pressure-resistant, and provides excellent heat dissipation.



Interface	USB3.2 Gen1x1 Type-C
Supported applications	SD & microSD [UHS-II Mode]SDR312, FD156 [UHS-I Mode]DDR200, SDR104, DDR50, SDR50 [HS/DS Mode]SDR25, SDR12
Supported OS	Windows 10 and later / macOS High Sierra 10.13 and later Interface: USB Type-C™ USB3.2 Gen1 port
Maximum transfer speed	[UHS-II]312MB/s [UHS-I]200MB/s
Operating Environment	[Temperature]5 to 35°C [Humidity]20 to 80%
Storage Environment	[Temperature]-20 ~ 50°C [Humidity]20 to 80%
Dimensions	51.4 (width) × 45.0 (height) × 12.0 (thickness) mm
Weight	43g
Accessories	USB-C to C cable (20cm) x 1, USB-A to C cable (20cm) x 1
Certification	RoHS, CE, FCC
Model number, JAN code	SE-RWMASDU2H3D2(4573574595525)
Warranty period	2 years from the date of purchase

ULTIMATE PRO CFexpress Type B & SD UHS-II Dual Slot Card Reader

USB3.2 Gen2 USBType-C

- CFexpress Type B compatible cards support maximum transfer speeds of up to 950MB/s;
SD UHS-II compatible cards support maximum transfer speeds of up to 312MB/s.
- USB3.2 Gen2 interface ensures high-speed and stable data transfer;
USB Type-C connection ensures compatibility with the latest devices.
- The body is made of high-quality aluminum alloy, providing durability, pressure resistance, and excellent heat dissipation.
- Equipped with LED lights for monitoring the operating status of the card.
- Dual slots allow simultaneous transfer of two cards (data can be copied between them).



Interface	USB3.2 Gen2 (USBType-C)
Supported OS	Windows 10 or later, macOS High Sierra 10.13 or later
対応カード	CFexpress Type B, SD UHS-II
Supported applications	CFexpress Type B SD UHS-II Mode : FD156/HD312 SD UHS-I Mode : DDR200/SDR104/DDR50/SDR50 SD HS/DS Mode : SDR25/SDR12
Maximum transfer speed	[CFexpress Type B]950MB/s [SD UHS-II]312MB/s
Operating Environment	[Temperature]5 to 35°C [Humidity]20 to 80%
Storage Environment	[Temperature]-20 ~ 50°C [Humidity]20 to 80%
Dimensions	Approx. 75.0 (width) × 50.0 (height) × 13.0 (thickness) mm
Weight	65g
Accessories	USB-C to USB-C cable (20cm) × 1, USB-A to USB-C cable (20cm) × 1, Magic tape × 1
Model number, JAN code	SE-RWCFX10GFSDU2(4573574595105)
Warranty period	1 years from the date of purchase

Card Reader

ULTIMATE PRO CFexpress Type B Card Reader

USB3.2 Gen2x1 Type-C

DGP2023 Record Item Division Card Reader/Writer Gold Award Winner

- Compatible with all CFexpress Type B memory cards, supporting up to 2TB
- 10Gbps high-speed transfer for a smooth workflow
- Plug and play, simply connect to the device for immediate use
- Includes 1 USB-C to C cable and 1 USB-A to C cable
- The body is made of high-quality aluminum alloy, providing durability, pressure resistance, and excellent heat dissipation



Interface	USB3.2 Gen2x1 Type-C
Compatible cards	CFexpress Type B
Supported OS	Windows 10 or later / macOS High Sierra 10.13 or later
Maximum transfer speed	1250MB/s(10Gbps)
Operating Environment	[Temperature]5 to 55°C [Humidity]20 to 80%
Dimensions	64.0 (width) × 45.0 (height) × 15.0 (thickness) mm
Weight	80g
Accessories	USB cable Type-C to C (20cm) × 1, USB cable Type-C to A (20cm) × 1
Certification	RoHS, CE, FCC
Model number, JAN code	SE-RWCFX10GC32G2(4573574592180)
Warranty period	2 years from the date of purchase

ULTIMATE SD & microSD UHS-I Dual Slot Card Reader

USB3.2 Gen1 Type-A/Type-C



Interface	USB3.2 Gen1 Type-A / Type-C
Supported OS	Windows 10 or later, Mac High Sierra 10.13 or later
Supported applications	SD & microSD UHS-I Mode : DDR200/SDR104/DDR50/SDR50 HS/DS Mode : SDR25/SDR12
Maximum transfer speed	170MB/s
Operating Environment	[Temperature]0 to 40°C [Humidity]0% to 70%
Storage Environment	[Temperature]-10 to 55°C [Humidity]0% to 60%
Dimensions	Approx. 73.0 (depth) × 17.0 (width) × 10.4 (height) mm
Weight	15g
Model number, JAN code	SE-RWMSDU1S1D2(4573574596409)
Warranty period	1 years from the date of purchase